

GENERAL DATASHEET

ANNA HEXAGON



TECHNICAL DESCRIPTION

Anna Hexagon luminaires. Direct-Indirect light distribution. Standard opal diffuser. Mounting types are Multi-Point Pendant, Single-Point Pendant, Spacers on Surface. Luminaire body surface in white, black, grey, anthracite, or custom RAL colors. Further Pont Light Selected Special Colors are also available. Driver is external, optionally switchable or dimmable (DALI, Push-Dim, Bluetooth). Color temperature 2700K, 3000K or 4000K. Binning \leq MacAdam 3. Color rendering CRI>80, CRI>90.

PROFILES

Profile sizes (width x height): 15x32 mm, 20x47 mm

LIGHT

Luminaire type: LED

Diffuser: Standard Opal

Control: ON-OFF, DALI, Push-Dim, Bluetooth

Beam Angle: Diffuse 110°

Color Temperature: 2700K, 3000K, 4000K

DIMENSIONS

Outer Diameter	Total Power	Total Light Output
Ø800 mm	48 W	4320 lm
Ø1200 mm	72 W	6480 lm
Ø1400 mm	84 W	7560 lm
Ø1800 mm	108 W	9720 lm

LUMINAIRE BODY

Material type: Aluminum, PMMA

Acoustic panel: Custom solutions available

Suspension cables: Custom length and type of suspension cables can be requested.

ELECTRICAL

Voltage: AC (230 volts)




BODY COLOR OPTIONS



LIGHTING TYPES



MOUNTING TYPES



The technical data values for luminous flux, electrical connected load, and colour temperature are indicative and subject to change. Definitive values can be confirmed by our representative upon request. No liability is assumed for typographical or printing errors. General terms and conditions of Pont Light Kft. apply.

© Pont Light Kft. · Nagyszombat utca 1. · 1036 Budapest · Hungary · www.pontlight.com