

# GENERAL DATASHEET

## ANETA



### TECHNICAL DESCRIPTION

Aneta round acoustic luminaires. Direct-Indirect light distribution. Opal diffuser. Surface in white, black, grey, anthracite, or custom RAL colors. Further Pont Light Selected Special Colors are also available. Selected Acoustic Panel Colors are available. Driver is external, optionally switchable, or dimmable (DALI, Push-Dim, Casambi). Color temperature 2700K, 3000K, or 4000K. Binning ≤ MacAdam 3. Color rendering CRI > 80, CRI > 90.

### PROFILES

Profile sizes: 15x88

### LIGHT

Luminaire type: LED

Diffuser: Standard Opal

Control: ON-OFF, DALI, Push-Dim, Bluetooth

Beam Angle: Diffuse 110°

Color Temperature: 2700K, 3000K, 4000K



### DIMENSIONS

Outer Dimensions	Total Power	Total Light Output
Ø800 mm	58 W	5220 lm
Ø1000 mm	72 W	6480 lm
Ø1200 mm	87 W	7803 lm
Ø1400 mm	101 W	9090 lm

### LUMINAIRE BODY

Material type: Aluminum, PMMA

Acoustic panel: Included, Custom solutions available

Suspension cables: Custom length and type of suspension cables can be requested.

### ELECTRICAL

Voltage: AC (230 volts)



### BODY COLOR OPTIONS



### LIGHTING TYPES



### MOUNTING TYPES

